




GENERATOR

Durable and High Performance Generator

- High Fuel Efficiency
- Ultimate Durability
 - 100% Copper Wire for Alternator
 - Anti-Rusty fuel tank
 - Full roll cage for ultimate protection
- Less Vibration & Quiet Operation



Copper Wire



KOSHIN
Engine



GV-3000

•All models have oil alert function.







GV-7600S



GV-7600S

■ Specification

Model		GV-3000	GV-7000S	GV-3200	GV-7600S
GENERATOR	Phase	Single			
	Voltage Regulation	AVR			
	Rated Output	2 kVA	5 kVA	2.3 kVA	5.5 kVA
	Maximum Output	2.2 kVA	5.5 kVA	2.5 kVA	6 kVA
	AC Rated Frequency	50 Hz		60 Hz	
	Rated Voltage	220 V			
	Rated Ampere	9.1A	22.7 A	10.5 A	25 A
	DC Output	12 V/8.3 A			
	Continuous Running Time rated load	9.5 h	7.5 h	6.3 h	5 h
	Tank Capacity	12.6 L	22.6 L	12.6 L	22.6 L
Receptacle	 European socket, CEE 7/4, 2pcs	 European socket, CEE 7/4, 1pc NEMA L6-30 Socket, 1pc	 BS1363, 2pcs OR CEE 7/4, 2pcs	 BS1363, 2pcs OR CEE 7/4 NEMA L6-30	
Model	Koshin K210	Koshin K420	Koshin K210	Koshin K420	
Type	Air-cooled, 4-stroke, OHV, single cylinder				
Displacement	212 cc	420 cc	212 cc	420 cc	
Oil Alert System	Standard				
Starting system	Recoil	Recoil/Electric starter	Recoil	Recoil/Electric starter	
Battery	—	Maintenance-free type	—	Maintenance-free type	
Wheel Kit	—	Standard	—	Standard	
Net Weigh	42 kg (93 lbs)	85 kg (187 lbs)	42.6 kg (94 lbs)	85 kg (187 lbs)	
Gross Weigh	44 kg (97 lbs)	87 kg (192 lbs)	45 kg (99 lbs)	89 kg (196 lbs)	
Dimensions LxWxH (mm)	615 × 445 × 457	695 × 534 × 547	615 × 445 × 457	695 × 534 × 547	
Packing Unit	1				

*GV-7000S/GV-7600S without battery